



Fleetguard lubricants are currently available in Africa and the Middle East only.

FLEETGUARD ENGINE OIL 10W-40 CI-4 UHPD

Article number CL41008

Product information

Ultra High Performance (UHPD) synthetic motor oil with low SAPS technology to protect exhaust systems. Meets Euro 4, 5 and 6 standards and ensures engine cleanliness, fuel savings, and extended drain intervals.

Physical properties

Property/Test	Value/Result	ASTM Standard
Color	Brown	
Density at 20°C	0.86 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	98.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.7 cSt	ASTM D 445
Viscosity Index	156	ASTM D 2270
Viscosity, dynamic (CCS)	5,466 cP	ASTM D 5293
Flash Point	232 °C	ASTM D 92
Sulfated Ash	1.0 wt%	ASTM D 874
Pour point	-39 °C	ASTM D 97
TBN mgKOH/g	9,9	ASTM D2896
Phosphorus %	0,075	ASTM D4951
Zinc %	0,084	ASTM D4951

Performance

DTFR 15C110 (MB 228.51)

Volvo VDS-3

Renault VI RLD-2

Mack EO-N

API CI-4

ACEA E6

ACEA E7

ACEA E9

ACEA E8/E11

MB 226.9

MAN M 3477

MAN M 3271-1

Renault RXD

Caterpillar ECF-1-A

CES 20076

CES 20077

MTU type 3.1

Renault RGD

DAF

Deutz DQC TTCD,

DQC IV-18 LA

Iveco 18-1804 TLS E6

JASO DH-2