



Atmus Filtration Technologies
Catenbergstraat 1, BE 2840 Rumst
Belgium, +32 2 808 76 83

Product Data Sheet

Fleetguard lubricants are currently available in Africa and the Middle East only.

FLEETGUARD GEAR OIL HPG EP 85W-140 GL-5

Article number CL41012

Product information

Mineral gear oil with the latest additive technology, offering metal-to-metal protection, corrosion resistance and thermal stability. Designed to lubricate hypoid gears, hub reductions, gearboxes, PTO (Power Take-off) gears, transfer cases, and differentials. Highly resistant to oxidative degradation and aging, Fleetguard gear oils do not affect seals. Suitable for API GL-5, MIL-L 2105-D and Mack GO-G specifications. 85W-140 can also be used where MB 235.0 is stipulated.

Physical properties

Property/Test	Value/Result	ASTM Standard
Color	Brown	
Density at 20°C	0.90 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	353.8 cSt	ASTM D 445
Viscosity, kinematic at 100°C	25.8 cSt	ASTM D 445
Viscosity Index	95.0	ASTM D 2270
Flash Point	201 °C	ASTM D 92
Pour point	-12 °C	ASTM D 97

Performance

API GL-5

MIL-L-2105 B/C/D

ZF TE-ML 05A

ZF TE-ML 12E